SAFETY PROTECTION SHEET

Distan 45





Display safety data sheet



Signal word

Hazard statements

Danger

H314 Causes severe skin burns and eye damage.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

General

Article no.

Use of the substance / mixture

1410056, 1410058, 1410059, 1410055

AISE-P314 - Surface disinfectant. Manual process.

AISE-P315 - Yfirborðssótthreinsir. Úðun og skolun,

AISE-P811 - Sótthreinsandi efni. Þokuúðun eða gösun. Hálfsjálfvirk aðferð.

First aid procedures

General

Inhalation

Skin contact

Eye contact

Ingestion

Acute symptoms and effects

Call a POISON CENTER or doctor/physician if you feel unwell. Show this SDS.

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Flush skin thoroughly with water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.

Promptly wash eyes with plenty of water while lifting the eye lids. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately! Continue flushing during transport to hospital.

Rinse mouth thoroughly. Drink a few glasses of water or milk. Get immediate medical advice/attention.

May cause severe eye damage. See further section 11.1 under "Potential Acute Effects"

Protective equipment

Symbols







Limitation of exposure on workplace

Eye protection

Suitable eye protection

Additional eye protection measures

Hand protection

Skin- / hand protection, long term contact

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Protective gloves and goggles are recommended. An eye wash bottle must be available at the work site.

Use approved safety glasses, goggles or face shield. Safety glasses should have side shields.

Safety glasses should have side shields.

Provide easy access to water supply and eye wash facilities.

Chemical resistant gloves required for prolonged or repeated contact.

Butylrubber:

Penetration time: >= 480 min Material thickness: >= 0,7 mm

Butyl rubber. Nitrile. Chloroprene rubber. Polyvinyl chloride (PVC). Rubber (natural, latex).

Under normal conditions of use respiration protection should not be required.

Suitable materials
Respiratory protection

Skin protection (except hands)

No special precautions.

Fire fighting measures

Suitable extinguishing media

Fire and explosion hazards

Fire fighting procedures

Personal protective equipment

Water spray, foam, dry powder or carbon dioxide.

No unusual fire or explosion hazards noted.

Fight fire with normal precautions from a reasonable distance.

Wear respiratory protection. Wear protective gloves / protective clothing / eye protection / face protection.

Preventitive Measures to contain emissions

General measures

Personal protection measures

Environmental precautionary measures

Cleaning method

Containment

Other instructions

Stop leak if safe to do so.

Wear protective gloves / protective clothing / eye protection / face protection.

Avoid release to the environment. Collect and dispose of spillage as indicated in section 13.

Absorb with sand or other inert absorbent.

Store in a closed container.

See section 8 and 13 for further details.

Responsible company

Company name

Country

Telephone number Emergency telephone Tandur h.f.

110 Reykjavík

ICELAND

00354 510 1200

112 NEYÐARNÚMER

543-2222 EITRUNARMIÐSTÖÐ