

25.03.2021

SAFETY PROTECTION SHEET

KLÓR 15%



Display safety data sheet



Signal word

Danger

Hazard statements

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.
EUH 031 Contact with acids liberates toxic gas.

General

Article no.	1440025, 1440026, 1440028, 1440029
CAS No.	7681-52-9
EC No.	231-668-3
Use of the substance / mixture	Disinfectant. Bleikingarefni

First aid procedures

General	Call a POISON CENTER or doctor/physician if you feel unwell. Show this SDS.
Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Skin contact	Flush skin thoroughly with water. Take off contaminated clothing and wash before reuse. Get immediate medical advice/attention.
Eye contact	Promptly wash eyes with plenty of water while lifting the eye lids. Remove contact lenses, if present and easy to do. Continue rinsing. Continue flushing during transport to hospital.
Ingestion	Rinse mouth thoroughly. Do not induce vomiting. Drink a few glasses of water or milk. Do not give victim anything to drink if he is unconscious. Get immediate medical advice/attention.
Acute symptoms and effects	Veldur alvarlegum bruna á húð og augnskaða See further section 11.1 under "Potential Acute Effects"
Information for health personnel	ÆTANDI EFNI: Inniheldur NATRÍUMHÝPÓKLÓRÍT!

Protective equipment

Symbols



Limitation of exposure on workplace

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Protective gloves and goggles are recommended. An eye wash bottle must be available at the work site.

Eye protection

Use approved safety glasses, goggles or face shield. Safety glasses should have side shields.

Suitable eye protection

Öryggisglæraugu skulu vera með hliðarhlífum.

Additional eye protection measures

Provide easy access to water supply and eye wash facilities.

Hand protection

Chemical resistant gloves required for prolonged or repeated contact.

Skin- / hand protection, short term contact

Nitril rubber:

Skin- / hand protection, long term contact	Penetration time: >= 30 min Material thickness: >= 0,4 mm
	Butylrubber: Penetration time: >= 480 min Material thickness: >= 0,7 mm
Suitable materials	Butyl rubber. Nitrile. Chloroprene rubber. Polyvinyl chloride (PVC). Rubber (natural, latex).
Respiratory protection	Under normal conditions of use respiration protection should not be required. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P2).
Skin protection (except hands)	Wear suitable protective clothing as protection against splashing or contamination.

Fire fighting measures

Suitable extinguishing media	Water spray, carbon dioxide, dry powder or polar resistant foam.
Fire and explosion hazards	OXIDISING!
Fire fighting procedures	Fight fire with normal precautions from a reasonable distance.
Personal protective equipment	Wear respiratory protection. Wear protective gloves / protective clothing / eye protection / face protection.

Preventitive Measures to contain emissions

General measures	Stop leak if safe to do so.
Personal protection measures	Wear protective gloves / protective clothing / eye protection / face protection.
Environmental precautionary measures	Avoid release to the environment. Collect and dispose of spillage as indicated in section 13.
Cleaning method	Absorb with inert, damp, non-combustible material, then flush area with water.
Containment	Store in a closed container.
Other instructions	See section 8 and 13 for further details.

Responsible company

Company name	Tandur h.f.
	110 Reykjavík
Country	ICELAND
Telephone number	00354 510 1200
Emergency telephone	543-2222 EITRUNARMÍÐSTÖÐ 112 NEYÐARNÚMER