SAFETY PROTECTION SHEET

Klórosan 20





Display safety data sheet



Signal word

Hazard statements

Danger

H315 Causes skin irritation.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects. EUH 031 Contact with acids liberates toxic gas.

General

Article no

Use of the substance / mixture

1440036, 1440038, 1440039

Disinfectant.

Bleaching agent.

First aid procedures

General

Inhalation

Skin contact

Eye contact

Ingestion

Acute symptoms and effects

Information for health personnel

Call a POISON CENTER or doctor/physician if you feel unwell. Show this SDS.

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Flush skin thoroughly with water. Take off contaminated clothing and wash before reuse. Get immediate medical advice/attention.

Promptly wash eyes with plenty of water while lifting the eye lids. Remove contact lenses, if present and easy to do. Continue rinsing. Continue flushing during transport to hospital.

Rinse mouth thoroughly. Do not induce vomiting. Drink a few glasses of water or milk. Do not give victim anything to drink if he is unconscious. Get immediate medical advice/attention.

May cause severe eye damage.

See further section 11.1 under "Potential Acute Effects"

Contains SODIUM HYPOCHLORITE! IF IN EYES: Remember to remove lenses if they are present. Ask patient. Continue eye rinsing/treatment. Call an eye specialist in all cases.

Protective equipment

Symbols







Limitation of exposure on workplace

Eye protection

Suitable eye protection

Additional eye protection measures

Hand protection

Skin- / hand protection, short term contact

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Protective gloves and goggles are recommended. An eye wash bottle must be available at the work site.

Use approved safety glasses, goggles or face shield. Safety glasses should have side shields.

Safety glasses should have side shields.

Provide easy access to water supply and eye wash facilities.

Chemical resistant gloves required for prolonged or repeated contact.

Nitril rubber:

Penetration time: >= 30 min

Material thickness: >= 0,4 mm Skin- / hand protection, long term contact

Butylrubber:

Penetration time: >= 480 min Material thickness: >= 0,7 mm

Respiratory protection Under normal conditions of use respiration protection should not be required.

In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment

with combination filter (type A2/P2).

Skin protection (except hands) Wear suitable protective clothing as protection against splashing or contamination.

Fire fighting measures

Suitable extinguishing media

Fire and explosion hazards

Fire fighting procedures

Personal protective equipment

Water spray, carbon dioxide, dry powder or polar resistant foam.

OXIDISING!

Fight fire with normal precautions from a reasonable distance.

Wear respiratory protection. Wear protective gloves / protective clothing / eye protection / face

Preventitive Measures to contain emissions

General measures

Personal protection measures

Environmental precautionary measures

Cleaning method

Containment

Other instructions

Stop leak if safe to do so.

Wear protective gloves / protective clothing / eye protection / face protection.

Avoid release to the environment. Collect and dispose of spillage as indicated in section 13.

Absorb with inert, damp, non-combustible material, then flush area with water.

Store in a closed container.

See section 8 and 13 for further details.

Responsible company

Company name

Tandur h.f.

110 Reykjavík

Country

ICELAND

Telephone number

00354 510 1200

Emergency telephone

(+354)-543-2222 EMERGENCY# POISON CENTER

112 POISON CENTER EMERGENCY#