SAFETY PROTECTION SHEET

Sótthreinsispritt





Display safety data sheet



Signal word

Hazard statements

Danger

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

General

Article no.

Use of the substance / mixture

1472022, 1472024

Disinfectant.

PC8 Biocidal Products (e.g. Disinfectants, pest control)

First aid procedures

General

Inhalation

Skin contact

Eye contact

Ingestion

Acute symptoms and effects

Call a POISON CENTER or doctor/physician if you feel unwell. Show this SDS.

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Flush skin thoroughly with water. If skin irritation occurs: Get medical advice/attention.

Promptly wash eyes with plenty of water while lifting the eye lids. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately! Continue flushing during transport to hospital.

Rinse mouth thoroughly. Do not induce vomiting. Get immediate medical advice/attention.

Irritation of eyes and mucous membranes, dilated pupils, respiratory irritation, breathing problems. Nausea/vomiting, depression, sleepiness, dizziness. See further section 11.1 under "Potential Acute Effects"

Personal protection equipment should be chosen according to the CEN standards and in discussion

with the supplier of the personal protective equipment. Protective gloves and goggles are

Use approved safety glasses, goggles or face shield. Safety glasses should have side shields.

recommended. An eye wash bottle must be available at the work site.

Chemical resistant gloves required for prolonged or repeated contact.

Provide easy access to water supply and eye wash facilities.

Protective equipment

Symbols





Safety glasses should have side shields.

Limitation of exposure on workplace

Limitation of exposure on workplace

Eye protection
Suitable eye protection

Additional eye protection measures

Hand protection

Skin- / hand protection, short term contact

Skin- / hand protection, long term contact

Material thickness: >= 0,4 mm

Penetration time: >= 30 min

Butylrubber:

Nitril rubber:

Penetration time: >= 480 min Material thickness: >= 0,7 mm

Respiratory protection

Under normal conditions of use respiration protection should not be required.

Skin protection (except hands)

In case of inadequate ventilation use suitable respirator.

Wear suitable protective clothing as protection against splashing or contamination.

Fire fighting measures

Suitable extinguishing media

Fire and explosion hazards

Fire fighting procedures

Personal protective equipment

Water mist, foam, dry powder or carbon dioxide.

Flammable liquid and vapour.

Fight fire with normal precautions from a reasonable distance.

Wear respiratory protection. Wear protective gloves / protective clothing / eye protection / face protection.

Preventitive Measures to contain emissions

General measures

Personal protection measures

Stop leak if safe to do so.

Wear protective clothing as described in Section 8 of this safety data sheet. Do not breathe vapour. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. Provide adequate ventilation.

Environmental precautionary measures

Containment

Other instructions

Avoid release to the environment. Collect and dispose of spillage as indicated in section 13.

Store in a closed container.

See section 8 and 13 for further details.

Responsible company

Company name

Tandur h.f.

110 Reykjavík

Country

ICELAND

Telephone number

00354 510 1200

Emergency telephone

112 POISON CENTER EMERGENCY#

(+354)-543-2222 POISON CENTER EMERGENCY#