

## SAFETY PROTECTION SHEET

## T-4



## Display safety data sheet



Signal word

Danger

Hazard statements

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

## General

Article no.

1476074, 1476076, 1476078

Use of the substance / mixture

Sanitizing cleaner

## First aid procedures

General

Call a POISON CENTER or doctor/physician if you feel unwell. Show this SDS.

Inhalation

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately!

Skin contact

Flush skin thoroughly with water. Take off contaminated clothing and wash before reuse. Get medical attention if irritation persists after washing.

Eye contact

Promptly wash eyes with plenty of water while lifting the eye lids. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. Continue flushing during transport to hospital.

Ingestion

Rinse mouth thoroughly. Do NOT induce vomiting. Drink a few glasses of water or milk. Get immediate medical advice/attention.

Acute symptoms and effects

See further section 11.1 under "Potential Acute Effects"

Information for health personnel

May cause severe skin and eye damage.

## Protective equipment

Symbols



Limitation of exposure on workplace

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Protective gloves and goggles are recommended. An eye wash bottle must be available at the work site.

Eye protection

Use approved safety glasses, goggles or face shield. Safety glasses should have side shields.

Suitable eye protection

Safety glasses should have side shields.

Additional eye protection measures

Provide easy access to water supply and eye wash facilities.

Hand protection

Chemical resistant gloves required for prolonged or repeated contact.

Skin- / hand protection, short term contact

Nitril rubber:

Penetration time:  $\geq 30$  minMaterial thickness:  $\geq 0,4$  mm

Skin- / hand protection, long term contact

Butylrubber:

Penetration time:  $\geq 480$  minMaterial thickness:  $\geq 0,7$  mm

Suitable materials	Butyl rubber. Nitrile. Chloroprene rubber. Polyvinyl chloride (PVC). Rubber (natural, latex).
Respiratory protection	Personal protection is normally not required. If ventilation is inadequate and exposure to liquid particles cannot be avoided, wear appropriate breathing apparatus using A2B2+P3 filter (fulfilling EN 137/EN 138). Avoid breathing vapours, spray or mists.

## Fire fighting measures

Suitable extinguishing media	Carbon dioxide or dry powder. Fight larger fires with water spray jet or alcohol-resistant foam
Fire and explosion hazards	No unusual fire or explosion hazards noted.
Fire fighting procedures	Fight fire with normal precautions from a reasonable distance.
Personal protective equipment	Wear respiratory protection. Wear protective gloves / protective clothing / eye protection / face protection.

## Preventitive Measures to contain emissions

General measures	Stop leak if safe to do so.
Personal protection measures	Wear protective gloves / protective clothing / eye protection / face protection.
Environmental precautionary measures	Avoid discharge into drains, water courses or onto the ground. Collect and dispose of spillage as indicated in section 13.
Cleaning method	Absorb in vermiculite, dry sand or earth and place into containers.
Containment	Store in a closed container.
Other instructions	See section 8 and 13 for further details.

## Responsible company

Company name	Tandur h.f.
	110 Reykjavík
Country	ICELAND
Telephone number	00354 510 1200
Emergency telephone	112 EMERGENCY SERVICES (+354)-543-2222 EMERGENCY# POISON CENTER