SAFETY PROTECTION SHEET

TK-OXOGEL



Display safety data sheet



Signal word

Hazard statements

Danger

H314 Causes severe skin burns and eye damage.

H400 Very toxic to aquatic life.

EUH 031 Contact with acids liberates toxic gas.

General

Article no.

1476136, 1476138, 1476139

Use of the substance / mixture

Foam cleaner.

First aid procedures

General

Inhalation

Skin contact

Eye contact

Ingestion

Acute symptoms and effects

Information for health personnel

Call a POISON CENTER or doctor/physician if you feel unwell. Show this SDS.

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Flush skin thoroughly with water. Take off contaminated clothing and wash before reuse. Get immediate medical advice/attention.

Promptly wash eyes with plenty of water while lifting the eye lids. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately! Continue flushing during transport to hospital.

Rinse mouth thoroughly. Drink a few glasses of water or milk. Get immediate medical advice/attention.

Causes severe skin burns and eye damage.

Ingestion will result in strong caustic effect on mouth and throat and to the danger of perforation of oesophagus and stomach.

 ${\tt CORROSIVE\ PRODUCT:\ Contains\ CAUSTIC\ SODA\ and\ SODIUM\ HYPOCHLORITE}$

Protective equipment

Symbols



Limitation of exposure on workplace

Eye protection
Suitable eye protection

Additional eye protection measures

Hand protection

Skin- / hand protection, short term contact









Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Protective gloves and goggles are recommended. An eye wash bottle must be available at the work site.

Use approved safety glasses, goggles or face shield. Safety glasses should have side shields.

Safety glasses should have side shields.

Provide easy access to water supply and eye wash facilities.

Chemical resistant gloves required for prolonged or repeated contact.

Nitril rubber:

Penetration time: >= 30 min Material thickness: >= 0,4 mm

Skin- / hand protection, long term contact

Butylrubber:

Penetration time: >= 480 min Material thickness: >= 0,7 mm

Suitable materials

Respiratory protection Under normal conditions of use respiration protection should not be required.

Butyl rubber. Nitrile. Chloroprene rubber. Polyvinyl chloride (PVC). Rubber (natural, latex).

In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment

with combination filter (type A2/P2).

Skin protection (except hands) Wear suitable protective clothing as protection against splashing or contamination.

Fire fighting measures

Suitable extinguishing media

Fire and explosion hazards

Fire fighting procedures

Personal protective equipment

Water spray, foam, dry powder or carbon dioxide.

No unusual fire or explosion hazards noted.

Fight fire with normal precautions from a reasonable distance.

Wear respiratory protection. Wear protective gloves / protective clothing / eye protection / face protection.

Preventitive Measures to contain emissions

General measures

Personal protection measures

Environmental precautionary measures

Containment

Other instructions

Stop leak if safe to do so.

Wear protective gloves / protective clothing / eye protection / face protection.

Avoid release to the environment. Collect and dispose of spillage as indicated in section 13.

Store in a closed container.

See section 8 and 13 for further details.

Responsible company

Company name

Country

Telephone number **Emergency telephone** Tandur h.f.

110 Reykjavík

ICELAND

00354 510 1200

112 NEYÐARNÚMER

543-2222 EITRUNARMIÐSTÖÐ