SAFETY PROTECTION SHEET

TS-PREMIXED





Display safety data sheet



Signal word

.

Hazard statements

Danger

H315 Causes skin irritation.

H318 Causes serious eye damage.

General

Article no.

Use of the substance / mixture

1476206, 1476208, 1476209

Disinfectant. AISE-P314 - Surface disinfectant. Manual process.

First aid procedures

General

Inhalation

Skin contact

Eye contact

Ingestion

Acute symptoms and effects
Information for health personnel

Call a POISON CENTER or doctor/physician if you feel unwell. Show this SDS.

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately!

Flush skin thoroughly with water. Get medical attention if irritation persists after washing.

Promptly wash eyes with plenty of water while lifting the eye lids. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. Continue flushing during transport to hospital.

Rinse mouth thoroughly. Do NOT induce vomiting. Drink a few glasses of water or milk. Get immediate medical advice/attention.

See further section 11.1 under "Potential Acute Effects"

IF IN EYES: Remember to remove lenses if they are present. Ask patient. Continue eye rinsing/treatment. Call an eye specialist in all cases.

Protective equipment

Symbols

Limitation of exposure on workplace

Eye protection
Suitable eye protection

Additional eye protection measures

Hand protection
Suitable materials
Respiratory protection







Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Protective gloves and goggles are recommended. An eye wash bottle must be available at the work site.

Use approved safety glasses, goggles or face shield. Safety glasses should have side shields.

Safety glasses should have side shields.

Provide easy access to water supply and eye wash facilities.

Chemical resistant gloves required for prolonged or repeated contact.

Butyl rubber. Nitrile. Chloroprene rubber. Polyvinyl chloride (PVC). Rubber (natural, latex).

Personal protection is normally not required. If ventilation is inadequate and exposure to liquid particles cannot be avoided, wear appropriate breathing apparatus using A2B2+P3 filter (fulfilling EN 137/EN 138). Avoid breathing vapours, spray or mists.

Fire fighting measures

Suitable extinguishing media Fire and explosion hazards Fire fighting procedures Personal protective equipment Carbon dioxide or dry powder. Fight larger fires with water spray jet or alcohol-resistant foam

No unusual fire or explosion hazards noted.

Fight fire with normal precautions from a reasonable distance.

Wear respiratory protection. Wear protective gloves / protective clothing / eye protection / face protection.

Preventitive Measures to contain emissions

General measures

Cleaning method

Other instructions

Containment

Personal protection measures

Environmental precautionary measures

Stop leak if safe to do so.

Wear protective gloves / protective clothing / eye protection / face protection.

Avoid discharge into drains, water courses or onto the ground. Collect and dispose of spillage as

indicated in section 13.

Absorb in vermiculite, dry sand or earth and place into containers.

Store in a closed container.

See section 8 and 13 for further details.

Responsible company

Company name

Tandur h.f.

110 Reykjavík

Country

ICELAND

Telephone number

00354 510 1200

Emergency telephone

112 POISON CENTER EMERGENCY#

(+354)-543-2222 POISON CENTER EMERGENCY#