SAFETY PROTECTION SHEET





Display safety data sheet

Display Salety uata sileet	
Signal word	Danger
Hazard statements	H314 Causes severe skin burns and eye damage.
General	
Article no.	1476084, 1476086, 1476088
Use of the substance / mixture	Cleaning agent. Hard surface cleaner.
First aid procedures	
General	Call a POISON CENTER or doctor/physician if you feel unwell. Show this SDS.
Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Skin contact	Flush skin thoroughly with water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Promptly wash eyes with plenty of water while lifting the eye lids. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately! Continue flushing during transport to hospital.
Ingestion	Rinse mouth thoroughly. Drink a few glasses of water or milk. Get immediate medical advice/ attention.
Acute symptoms and effects	May cause severe eye damage. See further section 11.1 under "Potential Acute Effects"
Information for health personnel	CORROSIVE: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Protective equipment

Symbols	
Limitation of exposure on workplace	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Protective gloves and goggles are recommended. An eye wash bottle must be available at the work site.
Eye protection	Use approved safety glasses, goggles or face shield. Safety glasses should have side shields.
Suitable eye protection	Safety glasses should have side shields.
Additional eye protection measures	Provide easy access to water supply and eye wash facilities.
Hand protection	Chemical resistant gloves required for prolonged or repeated contact.
Skin- / hand protection, short term contact	Nitril rubber: Penetration time: >= 30 min Material thickness: >= 0,4 mm
Skin- / hand protection, long term contact	Butylrubber: Penetration time: >= 480 min Material thickness: >= 0,7 mm
Suitable materials	Butyl rubber. Nitrile. Chloroprene rubber. Polyvinyl chloride (PVC). Rubber (natural, latex).

Respiratory protection	Under normal conditions of use respiration protection should not be required. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P2).	
Skin protection (except hands)	Wear suitable protective clothing as protection against splashing or contamination.	
Fire fighting measures		
Suitable extinguishing media	Water spray, foam, dry powder or carbon dioxide.	
Fire and explosion hazards	No unusual fire or explosion hazards noted.	
Fire fighting procedures	Fight fire with normal precautions from a reasonable distance.	
Personal protective equipment	Wear respiratory protection. Wear protective gloves / protective clothing / eye protection / face protection.	

Preventitive Measures to contain emissions

General measures	Stop leak if safe to do so.
Personal protection measures	Wear protective gloves / protective clothing / eye protection / face protection.
Environmental precautionary measures	Avoid release to the environment. Collect and dispose of spillage as indicated in section 13.
Containment	Store in a closed container.
Other instructions	See section 8 and 13 for further details.

Responsible company

Company name	Tandur h.f.
	110 Reykjavík
Country	ICELAND
Telephone number	00354 510 1200
Emergency telephone	112 EMERGENCY# (+354)-543-2222 POISON CENTER