

## SAFETY DATA SHEET

## EXAMPLE

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## Trade name

EXAMPLE

## ▼ Unique formula identifier (UFI)

A363-SRK3-QK9F-HVY8

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Relevant identified uses of the substance or mixture

## Thinner

## ▼ Use descriptors (REACH)

Sectors of use	Description
LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category	Description
PC9a	Coatings and Paints, Fillers, Putties, Thinners

Process category	Description
PROC10	Roller application or brushing
PROC11	Non industrial spraying

Environmental release category	Description
ERC8f	Wide dispersive outdoor use resulting in inclusion into or onto a matrix

## ▼ Uses advised against

Process category	Description
PROC7	Industrial spraying

## 1.3. Details of the supplier of the safety data sheet

## Company and address

**Only Fictive Chemicals Inc.**

Chemical Street 101

2020 Everywhere

Planet Earth

tel: +45 7240 1622

www.almego.com

## E-mail

info@chymeia.com

## Revision

8/3/2022

## SDS Version

3.0

## Date of previous version

7/22/2022 (2.0)

## 1.4. Emergency telephone number

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Emergency: 112 (24h service)

Hospital Malta Mater Dei, Medicines & Poisons information office: +356 2545 6508

See also section 4 "First aid measures".

## SECTION 2: Hazards identification

### ▼ 2.1. Classification of the substance or mixture

Flam. Liq. 3; H226, Flammable liquid and vapour.

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315, Causes skin irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

Aquatic Acute 1; H400, Very toxic to aquatic life.

Aquatic Chronic 1; H410, Very toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### ▼ Hazard pictogram(s)



#### Signal word

Danger

#### ▼ Hazard statement(s)

Flammable liquid and vapour. (H226)

May be fatal if swallowed and enters airways. (H304)

Causes skin irritation. (H315)

May cause drowsiness or dizziness. (H336)

Very toxic to aquatic life with long lasting effects. (H410)

#### Safety statement(s)

General

-

#### Prevention

Wear eye protection/protective gloves/protective clothing. (P280)

Wash hands and exposed skin thoroughly after handling. (P264)

#### Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)

Do NOT induce vomiting. (P331)

#### Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

#### Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

#### ▼ Hazardous substances

Solvent naphtha (petroleum), light aromatic

n-butyl acetate

### 2.3. Other hazards

#### Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

#### Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### ▼ VOC

VOC content: 530 g/L

MAXIMUM VOC CONTENT (Phase II, category B/a1: 850 g/L)

## SECTION 3: Composition/information on ingredients

### ▼ 3.2. Mixtures

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance	Identifiers	% w/w	Classification	Note
Zinc oxide	CAS No.: 1314-13-2 EC No.: 215-222-5 REACH: 01-2119463881-32 Index No.: 030-013-00-7	40-60%	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
Solvent naphtha (petroleum), light aromatic	CAS No.: 64742-95-6 EC No.: 265-199-0 REACH: 01-2119486773-24 Index No.: 649-356-00-4	≥10 - ≤25%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	[19]
Xylene	CAS No.: 1330-20-7 EC No.: 215-535-7 REACH: 01-2119488216-32 Index No.: 601-022-00-9	≥25 - ≤50%	Flam. Liq. 3, H226 Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332	[1]
n-butyl acetate	CAS No.: 123-86-4 EC No.: 204-658-1 REACH: 01-2119485493-29 Index No.: 607-025-00-1	≥25 - ≤50%	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336	[1]

-----

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[1] European occupational exposure limit

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – bring the label or this safety data sheet. The doctor can contact Hospital Malta Mater Dei, Medicines & Poisons information office: +356 2545 6508  
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.  
If skin irritation occurs: Get medical advice/attention.

#### Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

#### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>).

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure call 112 for emergencies otherwise contact Hospital Malta Mater Dei, Medicines & Poisons information office: +356 2545 6508 in order to obtain further advice.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Avoid inhalation of vapours from spilled material.

#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

#### 6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Ground and bond container and receiving equipment.
- Use explosion-proof [electrical/lighting/ventilating] equipment.
- Use non-sparking tools.
- Take action to prevent static discharges.
- It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
- Avoid direct contact with the product.
- Smoking, drinking and consumption of food is not allowed in the work area.
- See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

- Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
- Take action to prevent static discharges.
- Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

#### Recommended storage material

- Keep only in original packaging.

#### Storage temperature

- Dry, cool and well ventilated

#### Incompatible materials

- Combustible materials

### 7.3. Specific end use(s)

- This product should only be used for applications quoted in section 1.2

## SECTION 8: Exposure controls/personal protection

### ▼ 8.1. Control parameters

- Xylene  
Long term exposure limit (8 hours) (ppm): 50  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 221  
Short term exposure limit (15 minutes) (ppm): 100  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 442  
Annotations:  
"Skin" = Possibility of significant uptake through the skin.

- n-butyl acetate  
Long term exposure limit (8 hours) (ppm): 50  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 241  
Short term exposure limit (15 minutes) (ppm): 150  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 723

Protection Of The Health And Safety Of Workers From The Risks Related To Chemical Agents At Work Regulations, 5th September 2003 (Subsidiary Legislation 424.24)

### ▼ DNEL

n-butyl acetate

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	3.4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	7 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	6 mg/kg bw/day

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Short term – Systemic effects - Workers	Dermal	11 mg/kg bw/day
Long term – Local effects - General population	Inhalation	35.7 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	300 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	12 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	48 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	300 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	600 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	300 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	600 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	2 mg/kg bw/day
Short term – Systemic effects - General population	Oral	2 mg/kg bw/day

#### Solvent naphtha (petroleum), light aromatic

Duration	Route of exposure	DNEL
Long term – Local effects - General population	Inhalation	178.57 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	837.5 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	410 µg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	640 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	1066.67 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	1152 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m <sup>3</sup>

#### Xylene

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	125 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	212 mg/kg bw/day
Long term – Local effects - General population	Inhalation	65.3 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	221 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	65.3 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	221 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	260 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	442 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	260 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	442 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	12.5 mg/kg bw/day

#### Zinc oxide

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Duration	Route of exposure	DNEL
Long term – Systemic effects - Workers	Dermal	83 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	500 µg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	5 mg/m <sup>3</sup>

#### ▼ PNEC

##### n-butyl acetate

Route of exposure	Duration of Exposure	PNEC
Freshwater		180 µg/L
Freshwater sediment		981 µg/kg
Intermittent release (freshwater)		360 µg/L
Marine water		18 µg/L
Marine water sediment		98.1 µg/kg
Sewage treatment plant		35.6 mg/L
Soil		90.3 µg/kg

##### Xylene

Route of exposure	Duration of Exposure	PNEC
Freshwater		327 µg/L
Freshwater sediment		12.46 mg/kg
Intermittent release (freshwater)		327 µg/L
Marine water		327 µg/L
Marine water sediment		12.46 mg/kg
Sewage treatment plant		6.58 mg/L
Soil		2.31 mg/kg

##### Zinc oxide

Route of exposure	Duration of Exposure	PNEC
Freshwater		20.6 µg/L
Freshwater sediment		117.8 mg/kg
Marine water		6.1 µg/L
Marine water sediment		56.5 mg/kg
Sewage treatment plant		100 µg/L
Soil		35.6 mg/kg

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

### Hygiene measures

Take off contaminated clothing and wash it before reuse.

### Measures to avoid environmental exposure


Keep damming materials near the workplace. If possible, collect spillage during work.

### Individual protection measures, such as personal protective equipment


#### Generally

Use only CE marked protective equipment.


#### Respiratory Equipment

Type	Class	Colour	Standards	
A	Class 1 (low capacity)	Brown	EN14387	


#### Skin protection

Recommended	Type/Category	Standards	
Tyvek®	5, 6 / III	EN1149-1	

#### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388	

#### Eye protection

Type	Standards	
Wear safety glasses with side shields.	EN166	

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Colourless

#### Odour / Odour threshold

Solvent

#### pH

Testing not relevant or not possible due to nature of the product.

#### Density (g/cm<sup>3</sup>)



0,881

**Kinematic viscosity**

<0,07 cm<sup>2</sup>/s (40 °C)

**Particle characteristics**

Does not apply to liquids.

**Phase changes**

**Melting point/Freezing point (°C)**

-99

**Softening point/range (waxes and pastes) (°C)**

Does not apply to liquids.

**Boiling point (°C)**

Testing not relevant or not possible due to nature of the product.

**Vapour pressure**

1.5 kPa (20 °C)

**Relative vapour density**

Testing not relevant or not possible due to nature of the product.

**Decomposition temperature (°C)**

Testing not relevant or not possible due to nature of the product.

**Data on fire and explosion hazards**

**Flash point (°C)**

25

**Ignition (°C)**

Testing not relevant or not possible due to nature of the product.

**Auto flammability (°C)**

Testing not relevant or not possible due to nature of the product.

**Lower and upper explosion limit (% v/v)**

0.8 - 7.6

**Solubility**

**Solubility in water**

Testing not relevant or not possible due to nature of the product.

**n-octanol/water coefficient**

Testing not relevant or not possible due to nature of the product.

**Solubility in fat (g/L)**

Testing not relevant or not possible due to nature of the product.

**9.2. Other information**

**▼ VOC (g/L)**

530

**Other physical and chemical parameters**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No data available

**10.2. Chemical stability**

The product is stable under the conditions, noted in section 7 "Handling and storage".

**10.3. Possibility of hazardous reactions**

No special

**10.4. Conditions to avoid**

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

**10.5. Incompatible materials**

Combustible materials

**10.6. Hazardous decomposition products**

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## ▼ Acute toxicity

Product/substance	Xylene
Test method	OECD 403
Species	Rat, Brown Norway, male/female
Route of exposure	Inhalation
Test	LC50 (4 hours)
Result	6350 ppm
Other information	

Product/substance	Xylene
Test method	OECD 402
Species	Rabbit, New Zealand White, male/female
Route of exposure	Dermal
Test	LD50
Result	>4200 mg/kg
Other information	

Product/substance	Xylene
Test method	OECD 401
Species	Rat, Brown Norway, male/female
Route of exposure	Oral
Test	LD50
Result	3523 mg/kg
Other information	

Product/substance	n-butyl acetate
Test method	OECD 403
Species	Rat, Brown Norway, male/female
Route of exposure	Inhalation
Test	LC50 (4 hours)
Result	>21 mg/L
Other information	

Product/substance	n-butyl acetate
Test method	OECD 401
Species	Rabbit, Albino Himalaya, female
Route of exposure	Dermal
Test	LD50
Result	>14112 mg/kg
Other information	

Product/substance	n-butyl acetate
Test method	OECD 401
Species	Rat, Brown Norway, male/female
Route of exposure	Oral
Test	LD50
Result	10768 mg/kg
Other information	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

### Skin corrosion/irritation

Product/substance	n-butyl acetate
Test method	OECD 404
Species	Rabbit, New Zealand White, male/female
Duration	24 hours
Result	Adverse effect observed (Moderately irritating)
Other information	

Causes skin irritation.

#### ▼ Serious eye damage/irritation

Product/substance	Xylene
Test method	OECD 405
Species	Rabbit, New Zealand White, female
Duration	24 hours
Result	No adverse effect observed (Not irritating)
Other information	

Product/substance	n-butyl acetate
Test method	OECD 405
Species	Rabbit, New Zealand White, male/female
Duration	3 hours
Result	No adverse effect observed (Not irritating)
Other information	

### Respiratory sensitisation

Based on available data, the classification criteria are not met.

### Skin sensitisation

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

### Carcinogenicity

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

### Long term effects

**Irritation effects:** This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

**Neurotoxic effects:** This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

### Endocrine disrupting properties

No special

### Other information

Xylene has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

## ▼ 12.1. Toxicity

Product/substance	Solvent naphtha (petroleum), light aromatic
Test method	OECD 201
Species	Algae, Pseudokirchneriella subcapitata
Compartment	Freshwater
Duration	96 hours
Test	EC50
Result	19 mg/L
Other information	

Product/substance	n-butyl acetate
Test method	OECD 201
Species	Algae, Scenedesmus quadricauda
Compartment	Freshwater
Duration	72 hours
Test	EC50
Result	648 mg/L
Other information	

Product/substance	n-butyl acetate
Test method	OECD 202
Species	Daphnia, Daphnia magna
Compartment	Freshwater
Duration	48 hours
Test	EC50
Result	44 mg/L
Other information	

## ▼ 12.2. Persistence and degradability

Product/substance	Solvent naphtha (petroleum), light aromatic
Biodegradable	Yes
Test method	OECD 301 A
Result	>70%

Product/substance	Xylene
Biodegradable	Yes
Test method	OECD 301 D
Result	>60%

Product/substance	n-butyl acetate
Biodegradable	Yes
Test method	OECD 301 D
Result	80%

## ▼ 12.3. Bioaccumulative potential

Product/substance	Solvent naphtha (petroleum), light aromatic
Test method	
Potential bioaccumulation	Yes

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

LogPow	No data available
BCF	4
Other information	

Product/substance	Xylene
Test method	OECD 315
Potential bioaccumulation	Yes
LogPow	8,1 - 25,9
BCF	3.12
Other information	

Product/substance	n-butyl acetate
Test method	OECD 317
Potential bioaccumulation	No data available
LogPow	2,3
BCF	3.1
Other information	

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### 12.6. Endocrine disrupting properties

No special

#### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

### SECTION 13: Disposal considerations

#### ▼ 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

#### EWC code

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

#### Specific labelling

Not applicable






#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

### SECTION 14: Transport information

▼

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es) Labels: 3 Classification code: F1	14.4 PG*	14.5 Env**	Other information
ADR	UN1263	PAINT RELATED MATERIAL	Class: 3 Labels: 3 Classification code: F1  	III	Yes	Limited quantities: 5 L Tunnel restriction code: (E) See below for additional information.
IMDG	UN1263	PAINT RELATED MATERIAL	Class: 3 Labels: 3 Classification code: F1  	III	Yes	Limited quantities: 5 L EmS: F-E S-E See below for additional information.
IATA	UN1263	PAINT RELATED MATERIAL	Class: 3 Labels: 3 Classification code: F1 	III	Yes	See below for additional information.

\* Packing group

\*\* Environmental hazards

**Additional information**

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See the Dangerous Goods List, section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

**14.6. Special precautions for user**

Not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

No data available

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Restrictions for application**

Restricted to professional users.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

**Demands for specific education**

No specific requirements

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

▼ SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

E1 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 100 tonnes / (upper-tier): 200 tonnes

Additional information

Not applicable

▼ Sources

Protection Of Maternity At Work Places Regulations, 1st January 2001 (Subsidiary Legislation 424.11)

Control Of Major Accident Hazards Regulations, 1st June 2015 (Subsidiary Legislation 424.19)

Limitation Of Emissions Of Volatile Organic Compounds (Paints, Varnishes And Vehicle Refinishing Products) Regulations, 8th May 2012 (Subsidiary Legislation 549.71)

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H226, Flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H312, Harmful in contact with skin.

H315, Causes skin irritation.

H332, Harmful if inhaled.

H336, May cause drowsiness or dizziness.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

▼ The full text of identified uses as mentioned in section 1

LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites

PROC10 = Roller application or brushing

PROC11 = Non industrial spraying

PC9a = Coatings and Paints, Fillers, Putties, Thinners

ERC8f = Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the substance/mixture in regard of physical hazards has been based on experimental data.

#### ▼ The safety data sheet is validated by

CHYMEIA

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: MT-en